

Section 1 —  
Product Identification



# Material Safety Data Sheet

Sherwin-Williams Automotive Finishes Corp.  
101 Prospect Ave., N.W.  
Cleveland, OH 44115

Emergency telephone number  
(216) 566-2917  
Information telephone number  
(216) 566-2902  
Date of preparation  
December 28, 1998

©1998, The Sherwin-Williams Co.

## Cleaners - Solvent Based

**MET-S**

CAS No.	Section 2 — Hazardous Ingredients (percent by weight)	ACGIH		Vapor Pressure (mm Hg)	R1K213	R7K156	R7K158	R7K105	R7K106
		TLV <STEL>	OSHA PEL <STEL>						
64742-89-8	Lt. Aliphatic HC Solvent.	100	100	PPM	53.0			23	
64742-89-8	V. M. & P. Naphtha.	300 <400>	300 <400>	PPM	12.0	32	95		5
64742-88-7	Mineral Spirits.	100	100	PPM	2.0	54	5		
108-88-3	\$ Toluene.	50	100	PPM (Skin)	22.0	11		31	52
1330-20-7	\$ Xylene.	100 <150>	100 <150>	PPM	5.9			5	
138-86-3	Dipentene.	Not Established	Not Established	2.0		2			
67-56-1	\$ Methanol	200 <250>	200 <250>	PPM (Skin)	92.0			8	
67-63-0	2-Propanol	400 <500>	400 <500>	PPM	33.0			10	16
111-76-2	\$ 2-Butoxyethanol	25	25	PPM (Skin)	0.6			1	
67-64-1	Acetone.	500 <750>	1000 <750>	PPM	180.0			14	
108-10-1	\$ Methyl Isobutyl Ketone.	50 <75>	50 <75>	PPM	16.0			5	27
77-76-9	Dimethoxypropane.	Not Established	Not Established	76.0				2	
Weight per Gallon (lbs.)									
VOC (Volatile Organic Compounds) Total - lbs./gal.					6.35	6.40	6.21	6.64	6.87
VOC Less Water & Federally Exempt Solvents - lbs./gal.					6.35	6.40	6.20	5.71	6.86
Photochemically Reactive					No	No	No	Yes	Yes
Flash Point (°F)					100	50	44	21	39
DOL Storage Category					2	1B	1B	1B	1B
Flammability Classification (Flammable - Combustible)					Combustible	Flammable	Flammable	Flammable	Flammable
HMIS (NFPA) Rating (health - flammability - reactivity)					2 - 2 - 0	2 - 3 - 0	2 - 3 - 0	3 - 3 - 0	2 - 3 - 0
PAINT-SAFE® Personal Protection					J3	J3	J3	J3	J3

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

HEALTH: 2  
FIRE: 3  
REACTIVITY: 0

WAX & GREASE REMOVER

P  
E  
R  
C  
E  
N  
T  
B  
Y  
W  
E  
I  
G  
H  
T

## Section 3 — Physical Data

**PRODUCT WEIGHT** See TABLE  
**SPECIFIC GRAVITY** 0.75-1.03  
**BOILING RANGE** 132-395 °F  
**VOLATILE VOLUME** 100 %

## Section 4 — Fire And Explosion Hazard Data

**FLAMMABILITY CLASSIFICATION** See TABLE  
**FLASH POINT** See TABLE  
**LEL** 0.7  
**UEL** 36.5

### EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

### UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

### SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

## Section 5 — Health Hazard Data

### ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

### ACUTE Health Hazards

#### EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

#### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized

#### EMERGENCY AND FIRST AID PROCEDURES

**If INHALED:** If affected, remove from exposure. Restore breathing. Keep warm and quiet. Wash affected area thoroughly with soap and water.  
**If on SKIN:** Remove contaminated clothing and launder before re-use.  
**If in EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.  
**If SWALLOWED:** Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Give conscious patient several glasses of water. Seek medical attention.

### CHRONIC Health Hazards

Prolonged overexposure to solvent ingredients in R7K106 and R7K156 may cause adverse effects to the liver, urinary, cardiovascular, and reproductive systems. Prolonged overexposure to solvent ingredients in R7K105 and may cause adverse effects to the liver, urinary, bloodforming, cardiovascular, and reproductive systems. Prolonged overexposure to solvent ingredients in R7K213 and R7K158 may cause adverse effects to the liver and urinary systems. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

## Section 6 — Reactivity Data

### STABILITY — Stable

### CONDITIONS TO AVOID

None known.

### INCOMPATIBILITY

None known.

### HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

### HAZARDOUS POLYMERIZATION — Will Not Occur

## Section 7 — Spill or Leak Procedures

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

### WASTE DISPOSAL METHOD

Waste from these products may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA, 40 CFR 261). Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

## Section 8 — Protection Information

### PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

### VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

### RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

### PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

### EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

## Section 9 — Precautions

### DO NOT STORAGE CATEGORY — See TABLE

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and open flame.  
 During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.  
 Consult NFPA Code. Use approved Bonding and Grounding procedures.  
 Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

### OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

## Section 10 — Other Regulatory Information

### CALIFORNIA PROPOSITION 65

WARNING: These products, except R1K213, contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the products. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.