



MATERIAL SAFETY DATA

POSROC INC., FIFTY-FIVE SKYLINE DRIVE, PLAINVIEW, NEW YORK 11803 PHONE: 516-935-9100

EMERGENCY CONTACT: For chemical emergency spill, leak, fire, exposure or accident, call Chemtrec 800-424-9300 day or night.

10/12/90

TITEBOND LIQUID/BRUSH-BOND LIQUID/RENDEROC LIQUID/TITEBOND UNDERLAYMENT LIQUID/COLORBRITE/HUSH-TEX/RENDEROC C LIQUID/RENDEROC S LIQUID/RENDEROC SD LIQUID/RENDEROC HB LIQUID/NITOCOTE AR 311/NITOCOTE AR 310/NITOCOTE AR 312/ BRUSH-BOND CONCENTRATE/CRAFFITTI GUARD BASE COAT/NITOFLOUNDER-LAYMENT LIQUID/TITEBOND A/NITOBOND ACRYLIC/CERAMIX BLOCK FILLER/CERAMIX UNDERCOAT/RENDEROC HBA LIQUID/NITOCOTE EP BLOCKFILLER
Latex Emulsion

Fosroc Latex Emulsion

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	CAS NO.	%	CANCEROUS PER NTP/ IARC/ OSHA	OSHA PEL (PPM)	NIOSH CEILING (PPM)	ACGIH TLV (PPM)
Oxazolidene Family	97553-90-7	< 0.5	No	3	N.A.	N.A.

N.A. = Not Applicable/Not Available

SECTION III: PHYSICAL DATA

BOILING RANGE: 212°F VAPOR DENSITY: HEAVIER LIGHTER THAN AIR

EVAPORATION RATE: FASTER SLOWER THAN ETHER

PERCENT VOLATILE BY VOLUME: 45-85 SPECIFIC GRAVITY: 1.02-1.36

APPEARANCE & ODOR: Milky/pigmented liquid with slight ammoniacal odor.

SECTION IV: FIRE AND EXPLOSION DATA

DOT Category: Not Regulated Flash Point: N.A. LEL: N.A.

Extinguishing Media: N.A.

Special Firefighting Procedures: N.A.

Unusual Fire & Explosion Hazards: N.A.

Hazardous Decomposition Products: May form toxic materials - carbon monoxide, carbon dioxide and nitrogen oxides.

Target Organ Information: Overexposure may cause damage to eyes, skin and respiratory system.

SARA Statement: This product does not contain any chemicals which are reportable under Section 313 of Title III SARA.

SEE OTHER

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

Eyes

Can cause irritation, redness, tearing, blurred vision.

Skin

Can cause irritation, burns.

Inhalation

Can cause injury to lungs.

Ingestion

Can cause gastrointestinal irritation.

First Aid

Flush with large amounts of water, lift upper and lower lids occasionally, physician immediately.

Thoroughly wash exposed area with soap water. Remove contaminated clothing. Launder contaminated clothing before re-use.

Keep person warm, quiet and see physician immediately.

Do not induce vomiting, keep person warm, quiet, and see physician immediately.

SECTION IV: REACTIVITY DATA

Hazardous Polymerization: Cannot occur.

Stability: Stable

Incompatibility: Avoid contact with acid minerals.

SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:

Small Spill: Clean up by use of dustless methods.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection: NIOSH/MESA respirator (dust filter type in compliance with OSHA Std. 29 CFR 1910.134).

Ventilation: Provide sufficient mechanical (general) and/or local exhaust ventilation to maintain exposure below TLV's.

Protective Gloves: Wear chemical resistant gloves such as Buna-N.

Eye Protection: Chemical splash goggles in compliance with OSHA regulations as advised.

Other Protective Equipment: To prevent repeated or prolonged skin contact wear impervious clothing and boots.

SECTION IX: SPECIAL PRECAUTIONS

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this data sheet must be observed. Keep out of reach of children.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with Fosroc or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

WARRANTY

Fosroc warrants its products to be free of defects in material and workmanship. Under this warranty, we will provide, at no charge, product in conformity to replace any defective product. This warranty is void if the product is used in accordance with our written instructions and in applications recommended by us as to be suitable for this product. All claims concerning product defects must be made within 12 months of manufacture. Absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty is not transferable.

Jan 24, 92 15:53 NO.016

TEL: 1-516-935-9143

FOSROC INC USA