

HEALTH: 1
FLAMMABILITY: 1
REACTIVITY: 0

MATERIAL SAFETY DATA SHEET

Ashland Inc.

Page 001
Date Prepared: 01/14/02
Date Printed: 07/21/06
MSDS No: 505.0172170-002.010

NAPA EP WHEEL BEARING GREASE 12/1 LB

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: NAPA EP WHEEL BEARING GREASE 12/1 LB
General or Generic ID: PETROLEUM GREASE

Company

Ashland Inc.
Covington, KY

Emergency Telephone Number:

1-800-ASHLAND (1-800-274-5263)
24 hours everyday
Regulatory Information Number:
1-800-325-3751

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
PETROLEUM BASED LITHIUM COMPLEX GREASE		100.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation.

Skin

Can cause skin irritation.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material is not likely to be harmful.

Continued on next page

MATERIAL SAFETY DATA SHEET

Whland Inc.

Page 002

Date Prepared: 01/14/02

Date Printed: 07/21/06

MSDS No: 505.0172170-002.010

NAPA EP WHEEL BEARING GREASE 12/1 LB

Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea).

Target Organ Effects

No data

Developmental Information

No data

Cancer Information

No data

Other Health Effects

No data

Primary Route(s) of Entry

Skin contact.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Do not induce vomiting. Give one glass of milk or water, and get medical attention immediately. If possible, do not leave victim unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Continued on next page

MATERIAL SAFETY DATA SHEET

Whland Inc.

Page 003

Date Prepared: 01/14/02

Date Printed: 07/21/06

MSDS No: 505.0172170-002.010

NAPA EP WHEEL BEARING GREASE 12/1 LB

Note to Physicians

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin.

5. FIRE FIGHTING MEASURES

Flash Point

450.0 F (232.2 C) D-92

Explosive Limit

Not applicable

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 1, Reactivity - 0

Continued on next page

MATERIAL SAFETY DATA SHEET

Shland Inc.

Page 004

Date Prepared: 01/14/02

Date Printed: 07/21/06

MSDS No: 505.0172170-002.010

NAPA EP WHEEL BEARING GREASE 12/1 LB

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Sweep up material for disposal or recovery.

Large Spill

Shovel material into containers. Thoroughly sweep area of spill to clean up any residual material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Not applicable

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Wear safety glasses in compliance with OSHA regulations. (Consult your safety representative.)

Skin Protection

Wear resistant gloves such as: neoprene, Wear normal work clothing covering arms and legs.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Continued on next page

MATERIAL SAFETY DATA SHEET

hland Inc.

Page 005

Date Prepared: 01/14/02

Date Printed: 07/21/06

MSDS No: 505.0172170-002.010

NAPA EP WHEEL BEARING GREASE 12/1 LB

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

PETROLEUM BASED LITHIUM COMPLEX GREASE

No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for product) > 700.0 F (371.1 C) @ 760.00 mmHg

Vapor Pressure

Not applicable

Specific Vapor Density

> 1.000 @ AIR=1

Specific Gravity

.950 @ 60.00 F

Liquid Density

Not applicable

Percent Volatiles (Including Water)

No data

Evaporation Rate

Not applicable

Appearance

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

Whland Inc.

Page 006

Date Prepared: 01/14/02

Date Printed: 07/21/06

MSDS No: 505.0172170-002.010

NAPA EP WHEEL BEARING GREASE 12/1 LB

State

SEMISOLID

Physical Form

JELLY

Color

MEDIUM AMBER

Odor

No data

pH

Not applicable

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

Shland Inc.

Page 007

Date Prepared: 01/14/02

Date Printed: 07/21/06

MSDS No: 505.0172170-002.010

NAPA EP WHEEL BEARING GREASE 12/1 LB

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Continued on next page

MATERIAL SAFETY DATA SHEET

hland Inc.

Page 008

Date Prepared: 01/14/02

Date Printed: 07/21/06

MSDS No: 505.0172170-002.010

NAPA EP WHEEL BEARING GREASE 12/1 LB

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed() Fire() Reactive() Sudden
Release of Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page

SOURCE:ASHLAND INC WTR, EASYWTR