

STANADYNE**Material Safety Data Sheet**

Material Name: Performance Formula®

ID: 00292

HEALTH: 2
FLAMMABILITY: 2
REACTIVITY: 0***** Section 1 - Chemical Product and Company Identification *****

Product Numbers: 32943P/C/ZVW -340-002 (24/8 oz); 29409P/C (12/1 pint); 31845P/C (6/½ gal); 29410P/C (1/5 gal); 29411P/C (1/55 gal)

Chemical Name: Mixture

Product Use: Diesel Fuel Additive

Company Information

Stanadyne Corporation.

Phone: 1-800-842-2496 or 1-860-525-0821

92 Deerfield Road

Windsor, CT 06095-4209

Emergency # CHEMTREC 1-800-424-9300

***** Section 2 - Composition / Information on Ingredients *****

CAS#	Component	Percent (w/w)
64742-88-7	Solvent naphtha (petroleum) medium aliphatic	30-50
27247-96-7	2-Ethylhexyl nitrate	20-30
64742-95-6	Solvent naphtha (petroleum) light aromatic	10-20
64742-94-5	Naphtha (petroleum), heavy aromatic	3-7; 7-13
111-76-2	Ethylene glycol monobutyl ether	3-7
25551-13-7	Trimethylbenzene	3-7
95-63-6	1,2,4-Trimethylbenzene	1-5
108-67-8	1,3,5-Trimethylbenzene	1-3
100-41-4	Ethyl benzene	0.1-1
108-05-4	Vinyl acetate	0.1-1
91-20-3	Naphthalene	0.1-1

Component Related Regulatory Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product contains glycol ethers. The ranges noted above are per an interpretation contained in Health Canada Product Safety Bulletin effective 96/03/31.

***** Section 3 - Hazards Identification *******Emergency Overview**

DANGER Combustible liquid and vapor.

This product is irritating to the eyes, respiratory system and skin. Excessive inhalation of this material causes headache, dizziness and uncoordination. This product may cause nervous system effects including peripheral neuropathy. This product contains chemicals which have been shown to cause cancer in laboratory animals. Components of this product may have adverse effects on the blood-forming system. A component(s) of this product have been reported to cause birth defects and/or other reproductive harm. Irritating and toxic vapors may be released upon combustion of product. Extinguish fire with carbon dioxide, dry chemical, foam or water fog.

Potential Health Effects: Eyes

This product is irritating to the eyes. Effects may include a burning sensation, redness, swelling and/or blurred vision.

Potential Health Effects: Skin

This product is irritating to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. Product contains component(s) that can be harmful if absorbed through the skin. May cause allergic reaction in susceptible individuals.

Potential Health Effects: Ingestion

This product is harmful if swallowed. Ingestion of this product may cause headache, dizziness, uncoordination, and general weakness. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury, possibly death. Ingestion of this product may cause red blood cell hemolysis and possible liver and kidney injury.

Potential Health Effects: Inhalation

Harmful or fatal if inhaled. Inhalation of oil mists or fumes can cause irritation of the mucous membranes and upper respiratory tract. Excessive inhalation of this material causes headache, dizziness, nausea, stupor, and other central nervous system effects leading to visual impairment, difficulty in breathing, convulsions and uncoordination. Overexposure to organic nitrates may cause headache, nausea and decreased blood pressure. Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil granuloma formation, inflammation and increased incidence of infection.

HMIS Ratings: Health: 2* Fire: 2 Reactivity: 0 Pers. Prot.: impervious gloves/safety glasses (chemical goggles if splashing is possible)

Material Safety Data Sheet

Material Name: Performance Formula®

ID: 00292

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 4 - First Aid Measures ***

First Aid: Eyes

Flush eyes with large amounts of water for 15 minutes. Seek immediate medical attention.

First Aid: Skin

Remove contaminated clothing. For skin contact, wash immediately with soap and water. Get medical attention if skin disorder develops.

First Aid: Ingestion

If the material is swallowed, do not induce vomiting. Seek immediate medical attention or advice.

First Aid: Inhalation

If affected, remove individual to fresh air. If the affected person is not breathing, apply artificial respiration. Seek medical attention if symptoms persist. If overcome by vapor from hot product, immediately remove to fresh air and call a physician.

First Aid: Notes to Physician

Pulmonary aspiration hazard if swallowed, treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

Flash Point: 110° F (43.3° C) by Pinsky-Martens Closed Cup

OSHA Flammability Classification: Combustible

General Fire Hazards

Fire and explosion hazards are moderate when this product is exposed to heat or flame. Liquid can burn upon heating to temperatures at or above the flash point. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.

Hazardous Combustion Products

Irritating and toxic gases or fumes may be released during a fire. Upon combustion, this product may yield oxides of nitrogen, carbon monoxide, carbon dioxide, and/or other low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical, foam, carbon dioxide, water fog. Use water to cool fire-exposed containers and to protect personnel. Direct water spray or foam may cause frothing and spattering. If a leak or spill has not ignited, use water spray to disperse vapors and to flush spills away from exposure.

Fire Fighting Equipment/Instructions

Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products.

NFPA Ratings: Health: 2 Fire: 2 Reactivity: 0 Other:

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Containment Procedures

Stop the flow of material, if this can be done without risk.

Clean-Up Procedures

Absorb with non-flammable suitable absorbent such as sand or earth. Scoop up used absorbent into drums or other appropriate container.

Evacuation Procedures

Persons not wearing protective equipment should be excluded from area of spill until cleanup has been completed.

Special Procedures

Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Surfaces may become slippery after spillage. Wear appropriate protective equipment and clothing during cleanup. Do not allow the spilled product to enter public drainage systems or open watercourses. If product is spilled, notify appropriate authorities at the local, state, federal, and provincial levels.

Material Safety Data Sheet

Material Name: Performance Formula®

ID: 00292

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid prolonged or repeated skin contact with this material. Avoid getting this material into contact with your eyes. Avoid the generation of mists. Wash thoroughly after handling. Use this product with adequate ventilation. Discard any shoes or clothing items that cannot be decontaminated.

Storage Procedures

Do not store near heat, sparks, open flame or strong oxidizing agents. Do not store this material in open or unlabeled containers. Store drums in a covered area with secondary containment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. Follow appropriate grounding procedures.

*** Section 8 - Exposure Controls / Personal Protection ***

Exposure Guidelines

A: General Product Information

Follow all applicable exposure limits. Under conditions which may generate mists, the component supplier recommends the OSHA PEL of 5 mg/m³ and the ACGIH STEL of 10 mg/m³ for oil mists.

B: Component Exposure Limits

Compound	ACGIH		NIOSH		OSHA	
	TWA	STEL	TWA	STEL	TWA	STEL
Ethylene glycol monobutyl ether	20 ppm (S)	N/E	5 ppm (S)	N/E	50 ppm (S)	N/E
Trimethylbenzene	25 ppm	N/E	25 ppm	N/E	N/E	N/E
1,2,4-trimethylbenzene	25 ppm	N/E	25 ppm	N/E	N/E	N/E
1,3,5-trimethylbenzene	25 ppm	N/E	25 ppm	N/E	N/E	N/E
Vinyl acetate	10 ppm	15 ppm	4 ppm (C)	N/L	N/E	N/E
Naphthalene	10 ppm	15 ppm	10 ppm	15 ppm	10 ppm	N/E
Ethyl benzene	100 ppm	125 ppm	100 ppm	125 ppm	100 ppm	N/E

(S) - skin exposure

(C) - ceiling exposure

N/E - none established

Engineering Controls

Use general ventilation and use local exhaust, where possible, in confined or enclosed spaces.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses. Wear chemical goggles or faceshield if mist is likely to occur.

Personal Protective Equipment: Skin

Use impervious gloves. Wear oil-impervious garments if contact is unavoidable.

Personal Protective Equipment: Respiratory

In the event of excessive exposure to vapors/mists/fumes, use NIOSH/OSHA approved respiratory equipment. Respirator should be selected on the basis of form and concentration of contaminant.

Personal Protective Equipment: General

Use good hygiene when handling petroleum product. Launder contaminated clothing before reuse. Excessive misting may cause slippery floors - wear appropriate footwear. Eye wash fountains are recommended.

*** Section 9 - Physical & Chemical Properties ***

Appearance:	Amber colored	Odor:	Oil / solvent
Physical State:	Liquid	pH:	Not applicable
Solubility (H ₂ O):	Negligible	Specific Gravity:	0.87

Material Safety Data Sheet

Material Name: Performance Formula®

ID: 00292

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable

Incompatibility

This product may react with strong oxidizing agents.

Hazardous Decomposition

Decomposition of this product may yield oxides of nitrogen, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Hazardous Polymerization

Hazardous polymerization will not occur.

*** Section 11 - Toxicological Information ***

No data available on product as a whole.

CAS #	Component	Percent	LD50 - Oral (rat)	LD50 - Dermal (rabbit)	LC50 - Inhalation (rat)
111-76-2	Ethylene glycol monobutyl ether	3-7	470 mg/kg	220 mg/kg	450 ppm (4H)
25551-13-7	Trimethylbenzene	3-7	8970 mg/kg	Not available	Not available
95-63-6	1,2,4-Trimethylbenzene	=5	5 g/kg	Not available	18 g/m ³ (4H)
108-67-8	1,3,5-Trimethylbenzene	=3	Not available	Not available	24 g/m ³ (4H)
100-41-4	Ethyl benzene	=1	3500 mg/kg	17800 uL/kg	Not available
108-05-4	Vinyl acetate	=1	2920 mg/kg	2335 mg/kg	11400 mg/m ³ (4H)
91-20-3	Naphthalene	=1	420 mg/kg	> 20 g/kg	> 340 mg/m ³ (1H)

One or more components have produced damage after prolonged exposure in laboratory animals to one or more of the following: kidneys, liver, spleen, blood and/or circulatory system. Vinyl acetate, ethyl benzene and naphthalene have been shown to cause cancer in laboratory animals and are each classified Group 2B by IARC. Ethylene glycol monobutyl ether, vinyl acetate, and ethyl benzene have been linked with or reported to cause either birth defects and/or other reproductive harm.

A summary of toxicity data for components of this product is available upon request.

*** Section 12 - Ecological Information ***

No ecotoxicity or environmental fate data available on product as a whole.

A summary of aquatic toxicity data for components of this product is available upon request.

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

User must test waste using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous waste. If disposed of as shipped, this product may be considered a D001 ignitable waste.

Disposal Instructions

Dispose of waste material according to local, state, federal, and provincial environmental regulations. Do not allow this material to drain into sewers/water supplies. Material should be recycled if possible.

*** Section 14 - Transportation Information ***

General Transportation Information

NOTE: Information in this section (Section 14) is presented as a guide only. Requirements may vary depending upon package size and exceptions used, if any. Follow current, applicable requirements under DOT, TDG, IMO/IMDG, ICAO/IATA to ensure regulatory compliance.

Material Safety Data Sheet

Material Name: Performance Formula®

ID: 00292

U.S. Department of Transportation Regulations Ground Transportation
Not regulated based on Combustible Liquid exception [49CFR 173.150(f)].

Canadian TDG Regulations Ground Transportation
Not regulated based on exception [Part II, 2.23.2(1)].

International Transportation Regulations
ICAO/IATA

Flammable liquid, n.o.s. (contains petroleum naphthas, ethylene glycol monobutyl ether), 3, UN1993, PGIII

Label: Flammable Liquid

IMO/MDG

FLAMMABLE LIQUID, N.O.S. (contains petroleum naphthas, ethylene glycol monobutyl ether), 3, UN1993, PGIII
43.3° C c c) Marine Pollutant (2-ethyl-hexyl nitrate, petroleum naphthas)

EmS: F-E, S-E

Label: Flammable liquid

*** Section 15 – Regulatory Information ***

US Federal Regulations

A: General Product Information

Components listed in Section 2 of the MSDS are present on the TSCA Inventory.

This product contains naphthalene and less than 0.75% p-xylene which require TSCA §12(b) export notification.

B: Component Analysis

This material contains the following chemicals required to be identified under SARA Section 313 (40 CFR 372.65).

Ethylene glycol monobutyl ether (111-76-2) (glycol ether category)

1,2,4-Trimethylbenzene (95-63-6)

Ethyl benzene (100-41-4)

Naphthalene (91-20-3)

Vinyl acetate (108-05-4)

C: Component Marine Pollutants

This material contains 2-ethylhexyl nitrate which is required by US DOT to be identified as a marine pollutant.

Other Regulations

Components listed in Section 2 of the MSDS are present on the DSL and EINECS Inventories. This product has been classified in accordance with the hazard criteria required by the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*.

WHMIS Classification: B3, D2A, D1B, D2B

*** Section 16 - Other Information ***

Other Information

The information and recommendations presented in this Material Safety Data Sheet are based on sources believed to be reliable on the date hereof. Stanadyne Corporation makes no representation on its completeness or accuracy. This product is sold "as is" and it is the user's responsibility to determine the product's suitability for its intended use, the product's safe use, and the product's proper disposal. The statements and descriptions provided are informational only and no representations or warranties, either expressed or implied, of merchantability or fitness for a particular purpose or of any other nature are made with respect to the information provided in this Material Safety Data Sheet or to the product to which such information refers. Stanadyne Corporation neither assumes nor authorizes any other person to assume for it, any other or additional liability or responsibility resulting from the use of, or reliance upon, this information. Stanadyne Corporation assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.

Key/Legend

N = No; Y = Yes; ppm - parts per million; mg/m³ = milligrams per cubic meter of air. ACGIH = American Conference of Governmental Industrial Hygienists; OSHA = Occupational Safety and Health Administration; TLV = Threshold Limit Value; NIOSH = National Institute of Occupational Safety and Health; NTP = National Toxicology Program; IARC = International Agency for Research on Cancer; TSCA = Toxic Substance Control Act; DSL = Dangerous Substances List; EINECS = European Inventory of New and Existing Chemical Substances

Contact: For further information call 1-800-842-2496 or 1-860-525-0821

This is the end of MSDS # 00292